

DEMO SETS

| Code | Description | Includes |
|---------|---------------|---|
| 5025-A1 | 26 pieces set | Digital caliper, depth gauge, chamfer gauge, inside groove caliper, outside neck caliper, outside micrometer, internal micrometer, digital indicator, bore gauge, thickness gage, internal chamfer gage, digital level, plug gauge and ring gauge |
| 5025-B1 | 2 pieces set | Comparison gauge |
| 5025-C1 | 7 pieces set | Digital measuring tape, torque wrench, roughness tester, thickness gauge, hardness tester and videoscope |
| 5025-D | 1 piece set | Microscope |



















5025-A1/5025-C1/5025-D set box,
dimension: 635x475x250mm











5025-B1 set box,
dimension: 516x337x118mm

DETAILS

| Code | Includes | Description | Specification | Picture |
|---------|-------------|---|---|---------|
| 5025-A1 | 1108-150 | Digital caliper | 1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005" | |
| | 6144 | Accessory set or digital calipers | 1. Suitable for 0-150mm/0-6" and 0-200mm/0-8" digital calipers(thickness of lower jaws≤3.7mm) | |
| | 6147-A1 | Groove Points for digital calipers | 1. Suitable for 0-150mm/0-6" and 0-200mm/0-8" digital calipers(thickness of lower jaws≤3.7mm) | |
| | 1113-150 | Built-in wireless digital caliper | 1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005" | |
| | 1140-25WL | Built-in wireless mini digital depth gauge with round bar | 1. Range: 0-25mm/0-1" 2. Resolution: 0.01mm/0.0005" | |
| | 1141-150AWL | Built-in wireless digital depth gauge | 1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005" | |
| | 1148-200WL | Built-in wireless digital depth gauge with round depth bar | 1. Range: 0-200mm/0-8" 2. Resolution: 0.01mm/0.0005" | |
| | 1180-6WL | Built-in wireless digital chamfer gauge | 1. Range: 0-10mm/0-0.39" 2. Resolution: 0.01mm/0.0005" | |
| | 1176-150WL | Built-in wireless digital inside groove caliper | 1. Range: 9-150mm/0.35-6" 2. Resolution: 0.01mm/0.0005" | |
| | 1187-150AWL | Built-in wireless digital outside neck caliper | 1. Range: 0-150mm/0-6" 2. Resolution: 0.01mm/0.0005" | |
| | 1526-200WL | Built-in wireless digital caliper with interchangeable points | 1. Range: 0-224mm/0-8.8" 2. Resolution: 0.01mm/0.0005" | |
| | 3112-25WL | Built-in wireless waterproof digital outside micrometer | 1. Range: 0-25mm/0-1" 2. Resolution: 0.001mm/0.00005" | |

| Code | Includes | Description | Specification | Picture |
|-------------|---|--|--|---|
| 5025-A1 | 3113-20WL | Built-in wireless digital three points internal micrometer | 1. Range: 16-20mm/0.63-0.79" 2. Resolution: 0.001mm/0.00005" |  |
| | 3540-25WL | Built-in wireless digital depth micrometer | 1. Range: 0-25mm/0-1" 2. Resolution: 0.001mm/0.00005" |  |
| | 3507-25 | Bluetooth digital indicating micrometer | 1. Range: 0-25mm/0-1" 2. Resolution: 0.0001mm/0.000005" |  |
| | 3358-25AWL | Built-in wireless digital micrometers/snap gauge | 1. Range: 0-25mm/0-1" 2. Resolution: 0.001mm/0.00005" |  |
| | 2124-25+ 2508-10FWL | Pistol grip three points bore gauge | 1. Range: 20-25mm/0.78-1" 2. Resolution: 0.001mm/0.00005" |  |
| | 2508-10FWL | Built-in wireless digital indicator | 1. Range: 0-12.7mm/0-0.5" 2. Resolution: 0.001mm/0.00005" |  |
| | 2510-101F | Built-in wireless high precision digital indicator | 1. Range: 0-12.7mm/0-0.5" 2. Resolution: 0.001mm/0.00005" |  |
| | 2122-35A | Digital bore gauge | 1. Range: 18-35mm/0.7-1.3" 2. Resolution: 0.002mm/0.0001" or switch to 0.01mm/0.0005" |  |
| | 2871-101 | Digital thickness gauge | 1. Range: 0-10mm/0-0.4" 2. Resolution: 0.001mm/0.00005" |  |
| | 2937-101 | Digital internal chamfer gauge | 1. Range: 1-20mm/0.04-0.78" 2. Resolution: 0.01mm/0.0005" |  |
| | 2932-451 | Digital internal measuring gauge | 1. Range: 24-50mm/0.95-2" 2. Resolution: 0.001mm/0.00005" |  |
| | 2199-1 | Dual axis digital level and gyro angle meter | 1. Range: single axis level: 4x90°, dual axis level: +40°, gyro angle meter: 360° 2. Resolution: single axis level 0.01°, dual axis level 0.01° gyro angle meter 0.1° |  |
| | 4120-10-DLC | Metric thread ring gauge | 1. Nominal diameter: M10 2. Pitch: 1.5 |  |
| 4130-10-DLC | Metric thread plug gauge | 1. Nominal diameter: M10 2. Pitch: 1.5 |  | |
| 5025-B1 | 2252-120+ 2508-10FWL | Comparison gauge | 1. Range: 0-80mm/0-3,15" 2. Resolution: 0.001mm/0.00005" |  |
| | 2927-M200+ 2508-10FWL+ 2927-H+ 2927-S101+ 2927-S102+ 2927-S103+ 2927-S104+ 2927-J50+ 2927-D+ 2927-S201+ 2927-S201 | Universal comparison gauge | 1. Range: 0-200mm/0-8"(external diameter), 30-250mm/1.2-10"(internal diameter) 2. Resolution: 0.001mm/0.00005" |  |

| Code | Includes | Description | Specification | Picture |
|---------|-------------|---|--|---|
| 5025-C1 | 9570-A5 | Built-in wireless digital measuring tape | 1. Range: 5m 2. Resolution: 0.001m |  |
| | IST-42W20A | Built-in wireless digital torque wrench | 1. Range: 4-20N.m 2. Resolution (Ra): 0.01N.m |  |
| | ISR-C300WL | Built-in wireless Roughness tester | 1. Range: X axis:17.5mm, Z axis: 320μm (-160μm~160μm) 2. Resolution (Ra): 0.001μm |  |
| | 9501-1200WL | Built-in wireless coating thickness gauge | 1. Range: 0-1250μm 2. Resolution: 0.1μm (range<100μm), 1μm (range2100μm) |  |
| | ISU-800DWL | Built-in wireless ultrasonic thickness gauge | 1. Range: I-E 0.9-28mm/E-E 0.15-14mm 2. Resolution: 0.01mm/0.001mm |  |
| | HDT-LP200WL | Built-in wireless Portable leeb hardness tester | 1. Range: HL170-960/HRC 17-70/HRB 13-109/HRA 7-89/ HB 20-655/HV 80-940/HSD 32-99.5/σb(rm) 255-2639N/mm ² 2. Resolution: 1HLD/1HV/1HB/0.1HRC/0.1HRB/0.1HRA/ 0.1HSD/1σb |  |
| | ISV-K6015 | Videoscope | 1. Diameter: 6.0mm 2. Pixel: 0.92M |  |
| 5025-D | 5325-VM100 | Motorized zoom microscope | 1. Magnification: 10-68.5X 2. Resolution: 1920x1080 |  |