

AUTOMATIC ELECTRONIC ANALYTICAL BALANCE TEST SYSTEM CODE RBT-8312

CUSTOM
MADEHIGH
ACCURACYDATA
OUTPUT

ROBOT


- 6-axis industrial robot for high speed and precision, IP67, triple protection
- Electronic analytical balance test system automatically tests the weight of the workpiece and provides real-time feedback to the control system
- Control system Modbus Tcp via bus communication, high speed, high efficiency and easy to extend

ELECTRONIC ANALYTICAL BALANCE


- Downward-mounted electromagnetic sensor
- Aluminum alloy base, wind shield, three side glass sliding doors
- Zero-setting, weighing, subtracting tare value, counting
- Checking alarm, accumulation, animal scale, percentage display
- Peak (max.) and tracking mode
- Administrator permissions
- Recipe database: 99 recipes, up to 20 ingredients per recipe
- LCD display, with backlight
- Data output
- Automatic power off
- Unit: g, mg, ct, oz, ozt, dwt, mlb, GN, tj, gj, mo

operation process

- Step 1: Place the workpiece manually on the positioning block in the loading area and position it on the right side against the edge.
- Step 2: Press the reset button to return the robot and cylinder to the initial position.
- Step 3: Press the start button, the system prompts whether the workpiece is correctly placed and click OK.
- Step 4: The robot grabs the workpiece and places it onto the custom fixture.
- Step 5: Electronic analytical balance start measurement and output results.
- Step 6: The robot removes the workpiece and places the workpiece in the OK or NG station according to the measurement results.



weighing test interface



SPECIFICATION

Robot	Robot arm spreading	400mm
	Max working speed	7225mm/s
	Max weight of workpiece	3kg
	Repeat positioning accuracy	±0.02mm
	Number of control axis	4
	Communication protocols	Ethernet Modbus Tcp
Electronic analytical balance *	Weighing capacity	220g
	Minimal load	10mg
	Readability (d)	0.1mg
	Repeatability	±0.1mg
	Linearity	±0.3mg
	Calibration method	internal calibration
	Stabilization time	2.5s
	Dimension of pan (Ød)	Ø80mm

STANDARD DELIVERY

Robotic system	robot body
	robot control cabinet
	programming guide
Electronic analytical balance	1 pc
Control touch screen	1 set
Control box	1 set

*The quick measurement system is available in different models depending on the workpiece