




INFRARED THERMAL IMAGING CAMERA  
CODE 0235-HT480

IP54  
WATERPOOF

DATA  
OUTPUT



- Suitable for electric power, construction, electrical, mechanical, scientific research, etc.
- -20°C~650°C temperature measurement range, automatic switch, up to 2000°C with high temperature lens
- 4 hours operation time with interchangeable and rechargeable lithium-ion battery
- Software is included: support file management, thermal image analysis, video analysis, report editing, etc.
- Mobile APP is included: support real-time data and video transmission

SPECIFICATION

Infrared image	detector type	unrefrigerated detector, 7.5μm~14μm
	infrared resolution	480×360
	super resolution	upgrade to 960×720
	thermal sensitivity/NETD	<30mK
	infrared frame rate	50Hz
	spatial resolution/IFOV	0.68mrad
	aperture value	F1.0
	field of view	19°×14°
	minimum object distance	0.3m
	focusing mode	AF/continuous AF/laser assisted AF/touch AF/manual focus
	digital zoom	1.0x~8.0x

**SPECIFICATION**

<b>Image display</b>	<b>display screen</b>	4.3" touchscreen LCD, 800×480 pixel
	<b>visual camera</b>	3264×2448
	<b>image mode</b>	infrared, visual, fusion, pip, blending
	<b>color palettes</b>	white hot, black hot, rainbow, ironbow, red hot, fusion, rain, blue red
	<b>color highlight</b>	above, below, interval, insulation, condensation
<b>Measurement and analysis</b>	<b>measurement range</b>	support auto-switching: -20°C~150°C, 100°C~650°C, 300°C~2000°C (high temperature lens is required, included)
	<b>measurement accuracy</b>	±2°C or ±2%, whichever is greater
	<b>measurement tools</b>	center spot, hot spot, cold spot, user-definable: delta T, 10 spots, 5 rectangles, 5 circle, 1 line
<b>Function</b>	<b>laser</b>	indication: class 2, wavelength: 635nm, power: <1mW ranging: indoor 50m, outdoor 15m; accuracy: 0.1m
	<b>storage</b>	64G Micro SD card
	<b>image storage</b>	JPG (with temperature information)
	<b>video storage</b>	MP4 (without temperature information) and HRV (with temperature information)
	<b>WIFI</b>	802.11 b/g/n (2.4GHz and 5GHz)
	<b>bluetooth</b>	bluetooth 4.2
	<b>GPS and compass</b>	available
	<b>external interface</b>	TYPE-C, HDMI, SD card slot, 1/4" tripod mounting
	<b>battery type</b>	interchangeable and rechargeable lithium-ion battery, operating time 4 hours
<b>Physical parameter</b>	<b>charging time</b>	approximate 4 hours fully charged
	<b>operating environment</b>	-20°C~50°C, ≤95%RH
	<b>protection</b>	IP54, 2m drop test
	<b>dimension</b>	285×120×125mm
	<b>weight</b>	1.1kg

**STANDARD DELIVERY**

<b>Main unit</b>	1 pc
<b>High temperature lens</b>	1 pc
<b>64G SD card</b>	1 pc
<b>Lithium-ion battery</b>	2 pcs
<b>Desktop charger</b>	1 pc
<b>Power adapter</b>	1 pc
<b>Software</b>	1 pc

**OPTIONAL ACCESSORY**

<b>Tripod</b>	<b>0701-TR175</b>
---------------	-------------------