

BOURDON TUBE PRESSURE GAUGES (LIQUID FILLED)

CODE 5208-□□□□□

- stainless steel case, stainless steel ring, stainless steel connection
stainless steel bourdon tube
- Used for hydraulic and pneumatic systems, compressors, compressed air system,
shock-proof and pulse-proof
- Suitable for fluid medium which does not clog connection port or corrode stainless steel

STAINLESS
STEEL CASE

STAINLESS
STEEL RING


STAINLESS STEEL
CONNECTION

STAINLESS STEEL
BOURDON TUBE

CRIMP RING



5208-C4D3L1W1R19



Code example:

5208-C4D3L2W1R19	C4-connection thread 1/4BSP
	D3-dial size Ø63mm
	L2-back connection position
	W1-plastic material window
	R19-pressure range (0~60bar/0~850psi)

SPECIFICATION

Accuracy class	CL 2.5 for 40mm (1.5"), 50mm (2"); CL 1.6 for 63mm (2.5"), 100mm (4")
Liquid	silicone
Ambient temperature	-20°C~60°C (-4°F~140°F)
Medium temperature	≤60°C (140°F)

Process connection

C1	1/8BSP (Ø40mm, Ø50mm, Ø63mm)
C2	1/8ZG (Ø40mm, Ø50mm, Ø63mm)
C3	1/8NPT (Ø40mm, Ø50mm, Ø63mm)
C4	1/4BSP (Ø40mm, Ø50mm, Ø63mm, Ø100mm)
C5	1/4ZG (Ø40mm, Ø50mm, Ø63mm, Ø100mm)
C6	1/4NPT (Ø40mm, Ø50mm, Ø63mm, Ø100mm)
C7	3/8BSP (Ø100mm)
C8	3/8ZG (Ø100mm)
C9	3/8NPT (Ø100mm)
C10	1/2BSP (Ø100mm)
C11	1/2ZG (Ø100mm)
C12	1/2NPT (Ø100mm)

Dial size

D1	Ø40mm (1.5")
D2	Ø50mm (2")
D3	Ø63mm (2.5")
D4	Ø100mm (4")

Connection position

L1	bottom
L2	back
L3	back connection with front flange
L4	bottom connection with back flange

Window

W1	polycarbonate
W2	tempered glass

Pressure range

R1	(-1~0bar/-30~0inHg)
R2	(-1~2bar/-30~0inHg~30psi)
R3	(-1~4bar/-30~0inHg~60psi)
R4	(-1~7bar/-30~0inHg~100psi)
R5	(0~1bar/0~15psi)
R6	(0~1.4bar/0~20psi)
R7	(0~2bar/0~30psi)
R8	(0~2.5bar/0~35psi)
R9	(0~4bar/0~60psi)
R10	(0~7bar/0~100psi)
R11	(0~10bar/0~150psi)
R12	(0~11bar/0~160psi)
R13	(0~14bar/0~200psi)
R14	(0~16bar/0~230psi)
R15	(0~20bar/0~300psi)
R16	(0~25bar/0~350psi)
R17	(0~40bar/0~600psi)
R18	(0~55bar/0~800psi)
R19	(0~60bar/0~850psi)
R20	(0~70bar/0~1000psi)
R21	(0~100bar/0~1500psi)
R22	(0~140bar/0~2000psi)
R23	(0~160bar/0~2300psi)
R24	(0~200bar/0~3000psi)
R25	(0~250bar/0~3500psi)
R26	(0~280bar/0~4000psi)
R27	(0~350bar/0~5000psi)
R28	(0~400bar/0~6000psi)
R29	(0~600bar/0~9000psi)
R30	(0~700bar/0~10000psi)