

WATER TEST PRESSURE GAUGES

CODE 5210-□□□

- Plastic case, plastic window, brass connection
brass bourdon tube, with memory pointer
- Used for water test



5210-C1D2R3

Process connection

C1	1/4BSP (Ø50mm, Ø63mm)
C2	1/4ZG (Ø50mm, Ø63mm)
C3	1/4NPT (Ø50mm, Ø63mm)

Dial size

D1	Ø50mm (2")
D2	Ø63mm (2.5")

Pressure range


R1	(0~7bar/0~100psi)
R2	(0~11bar/0~160psi)
R3	(0~14bar/0~200psi)
R4	(0~20bar/0~300psi)

PLASTIC CASE

PLASTIC WINDOW

BRASS
CONNECTION

BRASS
BOURDON TUBE



Code example:

5210-C1D2R3	C1 -connection thread 1/4BSP
	D2 -dial size Ø63mm
	R3 -pressure range (0~14bar/0~200psi)

SPECIFICATION

Accuracy class	CL 2.5 for 50mm (2"); CL 1.6 for 63mm (2.5")
End connection	with 3/4" female thread copper alloy swivel connection
Ambient temperature	-20°C~60°C (-4°F~140°F)
Medium temperature	≤60°C (140°F)