## **4K AUTO FOCUS MEASURING MICROSCOPE** CODE 5315-S710

HDMI port

USB2.0 port

-I/O port
















■ Switchable LCD mode and computer mode

mode switch

step-zoom lens 0.75X~5X (zoom)


LED

USB3.0 port

power

LAN

- Take pictures or videos, save to memory card
- Measurement results can be sent to Excel
- Auto focus
- Automatic white balance and exposure





15.6" LCD (included)

fine focus knob (graduation: 2µm)

calibration plate (included)




1X camera adapter (optional)



2X auxiliary objective (optional)





#### **SPECIFICATION**

Z C		
Magnification	17.5X~109X (on 15.6" LCD)	
Sensor	1/1.7" CMOS	
Pixel	12M	
Resolution	4000×3000	
Frame rate	30fps	
Output	HDMI/USB/LAN	
Power supply	power adapter	
Dimension (L×W×H)	570×300×430mm	
Weight	15kg	

#### STANDARD DELIVERY

Main unit	1 pc
0.5X camera adapter	1 pc
1X auxiliary objective	1 pc
Calibration plate	1 pc
16G USB flash drive	1 pc
Mouse	1 pc
X-Y metal stage	1 pc

# MAGNIFICATION AND MEASURING ACCURACY (on 15.6" LCD)

(011 10:0 100)				
Objective magnification	Image magnification	Measuring accuracy		
0.75X	17.5X	±20µm		
1X	23X	±20µm		
1.5X	33X	±20µm		
2X	45X	±20µm		
2.5X	55X	±20µm		
3X	65X	±20µm		
3.5X	75X	±20µm		
4X	85X	±10µm		
4.5X	100X	±10µm		
5X	109X	±10µm		


#### MAGNIFICATION, FOCUS DISTANCE AND VIEW FIELD (on 15.6" LCD)

Specification	Camera adapter		
Opecification	0.5X (included)	1X (optional)	
Magnification	17.5~109X	35~218X	
Focus distance	73±2mm	73±2mm	
View filed	19.2×11.0~3.2×1.9mm	9.6×5.5~1.6×0.9mm	

#### **OPTIONAL ACCESSORY**

1X camera adapter	ISM-DL-CA1X
2X auxiliary objective	ISM-DL-OB2X
Computer	ISM-DL-COMPUTER
LED light	page 626~627
Auxiliary objective	page 628

#### SOFTWARE FOR LCD (INCLUDED)



### SOFTWARE FOR COMPUTER (INCLUDED)

