



## HIGH POWER DC POWER SUPPLIES

- High precision and low ripple
- OVP/OCP/OPP/OTP protection
- 1U half rack, suitable for system integration
- Remote compensation function
- Various communication interfaces
- Customized specifications are available



Unit: mm



### SPECIFICATION

| Code                 | 9916-HC1K81                                    | 9916-HC1K82   | 9916-HC1K83   | 9916-HC1K84  | 9916-HC1K85    |
|----------------------|--|---------------|---------------|--------------|----------------|
| Rate output voltage  | 0~30V  | 0~60V         | 0~100V        | 0~150V       | 0~300V         |
| Rate output current  | 0~60A  | 0~30A         | 0~18A         | 0~12A        | 0~6A           |
| Maximum output power | 1800W  |               |               |              |                |
| Voltage              | Setting resolution                             | 1mV           | 10mV          |              |                |
|                      | Setting accuracy                               | ≤0.05%+0.2%FS | ≤0.05%+0.1%FS |              | ≤0.05%+0.05%FS |
|                      | Readback resolution                            | 1mV           | 10mV          |              |                |
|                      | Readback accuracy                              | ≤0.05%+0.2%FS | ≤0.05%+0.1%FS |              | ≤0.05%+0.05%FS |
|                      | Load regulation                                | ≤0.05%+20mV   | ≤0.1%+20mV    | ≤0.1%+30mV   |                |
|                      | Line regulation                                | ≤0.05%+20mV   | ≤0.1%+20mV    | ≤0.1%+30mV   |                |
|                      | Ripple   | ≤30mVrms      | ≤60mVrms      | ≤80mVrms     | ≤100mVrms      |
| Current              | Setting resolution                             | 1mA           |               |              |                |
|                      | Setting accuracy                               | ≤0.1%+0.05%FS | ≤0.1%+0.1%FS  | ≤0.1%+0.2%FS | ≤0.05%+0.5%FS  |
|                      | Readback resolution                            | 1mA           |               |              |                |
|                      | Readback accuracy                              | ≤0.1%+0.05%FS | ≤0.1%+0.1%FS  | ≤0.1%+0.2%FS | ≤0.1%+0.5%FS   |
|                      | Load regulation                                | ≤0.05%+20mA   | ≤0.1%+20mA    | ≤0.1%+30mA   |                |
|                      | Line regulation                                | ≤0.05%+20mA   | ≤0.1%+20mA    | ≤0.1%+30mA   |                |
|                      | Ripple   | ≤30mA rms     | ≤60mA rms     | ≤80mA rms    | ≤100mA rms     |
| Work condition       | temperature: 0°C~40°C, humidity: 20%RH~80%RH   |               |               |              |                |
| Storage condition    | temperature: -10°C~55°C, humidity: 10%RH~90%RH |               |               |              |                |
| Cool system          | fan cool                                       |               |               |              |                |
| Power supply         | 220V±10%, 50Hz/60Hz                            |               |               |              |                |
| Dimension (W×D×H)    | 215x405.5x44mm                                 |               |               |              |                |
| Weight               | 4.5kg  |               |               |              |                |