



DIGITAL SHORE DUROMETERS







- According to ISO868, ISO7619, ASTM D 2240
- Average and peak (max.) mode
- Dwell time is adjustable
- Tolerance testing
- 500 memories
- Wireless connection to printer
 Handhold use or work with test stand (code ISH-DS-STANDA)
- Automatic power off







calibration block (included)



printer (optional)

SPECIFICATION

| SPECIFICATION | _ | | |
|---------------------|------------------------------------|------------------------------------|--|
| Code | ISH-DSA | ISH-DSD | ISH-DSOO |
| Unit | Shore A | Shore D | Shore OO |
| Test material | soft plastic, soft rubber, etc. | hard plastic, hard rubber, etc. | very soft plastic, rubber, sponge, textile, etc. |
| Measuring range | 0~100HA* | 0~100HD * | 0~100HOO |
| Resolution | 0.1HA | 0.1HD | 0.1HOO |
| Accuracy | ±1HA | ±1HD | ±1H00 |
| Indenter protrusion | 2.5mm | | |
| Output | wireless and USB | | |
| Power supply | built-in rechargeable battery | | |
| Dimension | 153×50×29mm | | |
| Weight | 170g | | |

^{*} Use **ISH-DSD** when measuring result is higher than 90HA Use ISH-DSA when measuring result is lower than 20HD

STANDARD DELIVERY

| STANDARD DELIVERT | |
|------------------------|------|
| Main unit | 1 pc |
| Calibration block | 1 pc |
| Software and USB cable | 1 pc |
| AC/DC adapter | 1 pc |

OPTIONAL ACCESSORY

| <u> </u> | | |
|------------|----------------|--|
| Printer | ISH-DS-PRINTER | |
| Test stand | ISH-DS-STANDA | |