



## SURFACE PROFILE MEASURING MACHINE **CODE SPM-1000**

- Software is included, for surface profile measurement and data output
- Probe compensation
- Output as format txt, csv, etc.
- Large range design, the leverage ratio is 1:2.2, maintain the original accuracy of the sensor
- The overall structure of the Z-axis sensor does not have any elastic components, ensuring the measuring force is constant regardless the position of probe



calibration





dimension measurement

data output

## **SPECIFICATION**

X axis measuring range	140mm
X axis resolution	0.1μm
X axis straightness	0.5µm/100mm
X axis moving speed	0.1~10mm/s
Z axis measuring range	±20mm
Z axis resolution	0.05µm
Z axis moving speed	0.5~10mm/s
Linear accuracy	±(0.8+ 0.05H )µm, H is measuring height in mm
Angular measuring accuracy	±2'
Arc measuring accuracy	±(2+R/8)µm, R is 2~10mm standard ba <b>ll</b>
Radius of probe tip	25µm
Moving direction	backward
Measuring force	6.9~9.8mN
Measuring unit	mm/inch
Traceable angle	72° (upward), 87° (downward)
Drive mode	motor
Travel of Z axis	430mm
Dimension (L×W×H)	1200×700×1780mm
Power supply	220±5%V, 50Hz
Weight	320kg





standard balls (included)



standard blocks (included)



standard shaft (included)

STANDARD DELIVERY		
Main unit	1 pc	
Standard probe and arm	1 pc of each	
Standard block	2 pcs	
Standard ball	2 pcs	
Standard shaft	1 pc	
Stage	1 pc	
Vise	1 pc	
Computer	1 pc	
Measurement software	1 pc	
Printer	1 pc	
Installation tools	1 set	






stage (included)

vise (included)

## **OPTIONAL ACCESSORY**

	Probe	refer to details



measure the contour of holes in radial direction