

## ELECTRIC THERMOSTATIC WATER BATHS

- Suitable for biomedical industry, chemical industry, education and scientific research, etc.
- Stainless steel inner tank, rounded corner design, multiple test port cover dimensions available
- Intelligent temperature controller, provides precise and reliable temperature control, features PID auto-tuning function
- Equipped with over-temperature alarm function to ensure samples safety



WTB-A101

### SPECIFICATION

Code	WTB-A101	WTB-A102	WTB-A103	WTB-A104
Temperature range	RT+10°C~100°C			
Temperature resolution	0.1°C			
Temperature deviation	±1°C			
Temperature fluctuation	±0.5°C			
Temperature uniformity	≤1°C			
Test port	2pcs	4pcs	6pcs	8pcs
Test port cover dimension	Ø45mm, Ø65mm, Ø85mm, Ø105mm, Ø125mm			
Material	shell: cold-rolled steel plate with powder coating; inner tank, cover plate, partition plate: stainless steel plate			
Power supply	AC220V, 50Hz			
Power	500W	800W	1500W	2000W
Working area dimension (L×W×H)	240×140×110mm	300×240×110mm	500×300×150mm	550×350×150mm
External dimension (L×W×H)	360×190×205mm	420×290×205mm	655×350×205mm	725×420×210mm
Weight	4kg	6kg	9kg	11kg

### STANDARD DELIVERY

Main unit	1 pc
Partition plate	1 pc
Cover plate	1 pc
Test port cover	1 set